

Pager

ZKRUNCIPPOSPG10

ZKR

Technical Specification

ZKRUNCIPPOSPG10

<i>Protocol</i>	POCSAG
<i>Weight</i>	68 g
<i>Width</i>	76 mm
<i>Depth</i>	18 mm
<i>Height</i>	53 mm
<i>Frequency Range</i>	433-434 MHz
<i>Cap Codes</i>	8
<i>Receiver Type</i>	Synthesized or Crystal
<i>Baud Rate</i>	512, 1200, 2400 bps
<i>Paging Sensitivity</i>	-110DB @ 512 bps / -108DB @ 1200 bps / -106DB @ 2400 bps
<i>Channel Spacing</i>	25 KHz or 12.5KHz
<i>Frequency Deviation</i>	+/-4.5 KHz
<i>Frequency Stability</i>	+/- 10 PPM
<i>Selectivity</i>	> 55dB
<i>Image Rejection</i>	> 52dB
<i>Spurious Rejection</i>	> 55dB
<i>Intermediation</i>	50dB
<i>Alert Tone Loudness</i>	75dB+ @ 12 inch
<i>Display</i>	16 characters / line, 22 characters max
<i>Memory Capacity</i>	up to 3000 characters
<i>Messages</i>	19 max
<i>Battery Type</i>	Single AAA
<i>Low Battery Alert Level</i>	1.1V
<i>Operating Temperature</i>	-10°C + 50°C