Comfort 10" Room Control Unit






40.00 mm

The Comfort Room Control Unit ensures communication between the Nurse Control Panel and the call units in patient rooms. This unit is suitable for surface montage. The unit supports up to 6 Call Units by default, and features a 10" touchscreen and a built-in Mifare card reader, which nurses use to verify their identity when responding to calls. All cards read by the unit are checked for authorization.

The Room Control Unit can be used to initiate and terminate emergency code calls (Code Blue-Cardiac Arrest etc.), assist calls, and consultation calls. It allows routine controls the staff to use their cards to log into the room without an active call. The unit logs all activities to the server with timestamps and ID information. If the server connection is interrupted, the Room Control Unit will independently log up to 99 calls until server connection is reestablished. On the Comfort VoIP Room Control Unit, you can make voice calls with other SIP devices on the system.





Technical Specification

ZKRUNCIPCNFRMC002

10" IPS Color Touch Screen Linux
500 g
265 mm
40 mm
210 mm
1024x768 IPS
ARM Cortex A7 1.2 Ghz
128 MB RAM - 8 GB ROM
Full Duplex SIP
English, Spanish, Russian, Turkish Custom
110-240 V or PoE
-10°C +60°C / % 30 %80 RH
PC-ABS-FR
MIFARE Card Reader
3 Watt
6xRJ45 for Call Units, 1xRJ45 for Over Door Light, 1xPower In, 1xEthernet, 1xSD Slot
White
12 V

- PoE (Power Over Ethernet) or 110-240 V
- VoIP Full Duplex SIP
- Conference Call
- Internal and External Call (with tracking system for billing)
- Built-in Mifare card Reader
- Timer/Stopwatch
- Menu option for personalized task lists based on personnel ID
- Can display hospital advertisements or other videos
- Can display educational videos for specific healthcare procedures